



WEIGHING DISHES "ACCU-WEIGH"

Anti static. Reproducible tare weighing.
Contamination free. Large selection of sizes.

Common features:

Made from high density polystyrene with flat base, round edge, contamination free surface and hydrophilic. Flexible in form for easy manipulation of the sample either liquid or solid.

Manufactured in two forms:

- Diamond form, colours white and black.
- Square form, colour white.

Part No.	Form	Capacity	Height / Width / Depth	Weight	Colour
5726004	Diamond	5	3.8 31 54	0.25	White
5726005	Diamond	5	3.8 31 54	0.25	Black
5726006	Diamond	30	13.5 55 85	1.00	White
5726007	Diamond	30	13.5 55 85	1.00	Black
5726008	Diamond	100	20 92 132	2.6	White
5726009	Diamond	100	20 92 132	2.6	Black
5726010	Square	7	8.5 44 44	0.65	White
5726011	Square	100	24 80 80	2.2	White
5726012	Square	250	24 134 134	6.1	White

Comes in packets of 100 units.



ALUMINIUM WEIGHING BOATS

Static free, pressed dishes with rolled edge.

Withstands temperatures up to 450 °C.

Due to their form the dishes can be used one on top of another to protect samples. Suitable for testing, solid samples and mixtures of emulsions for moisture content, by differential weight loss method.

Useful for weighing, comparing, freezing or evaporation.

Consumable, single use.

Part No.	Thickness mm	Height / Ø (usable) mm	Comes in
5726000	0.2	5 42	packets of 112 units
5726001	0.2	10 57	packets of 110 units



ANTIVIBRATION BALANCE TABLE

Formica covered metal table with central polished granite plate to support the balance, mounted on silent blocks.

Adjustable shock device. Maximum weight 40 Kg.

Part No.	Height / Width / Depth (exterior) cm	Height / Depth (balance support) cm	Weight Kg
5838101	80 90 70	45 39	70



BALANCE DENSITY MEASUREMENT "PR-SE" (PATENTED)

Applications: System for reading the density of liquids using the immersion of a glass sinker of known volume. Can be used for opaque and viscous liquids for all classes of liquid.

Features: Made of borosilicate glass of low dilatation coefficient and a constant volume. Mode of operation:

- Locate the tube with liquid on an electronic balance.
- Push the TARE to achieve a zero stable reading
- Introduce and submerge the measuring suspended sinker centrally without tilting the tube, keep suspended.

At this moment the screen will indicate the DIFFERENTIAL WEIGHT, that is exactly the same as the density of the liquids multiplied by 10.

To obtain a density value in mS, it is necessary to have a balance with a minimum resolution of 0.01 g.

Part No.	Density interval g/ml	Maximum tolerance error g/ml	Temperature assay/reference °C
5600000	0.600 - 2.000	±0.0005	20 / 20