

GFL

1

Water Baths 1031 and 1032 for Fume Hoods

- Special baths that are preferably used for protected applications in fume hoods (digestories).
- Temperature range from approx. 5 °C above ambient to boiling point, temperature regulation through tension thermostat. Heating element protected by over-temperature cut-out.
- Bath, removable recessed lid with holes and perforated floor above the heating element are made of stainless steel.
- The adjustable water level regulator at the right-hand side of the unit is part of the standard scope of supply.
- The openings in the lid are covered by sets of rings made of heat-resistant plastic material.
- Four non-slip plastic feet ensure great stability.
- Mains supply: 230 V*, 50 / 60 Hz.



Type	Openings with sets of rings	Openings- ø mm	Working height mm	Outside dimensions (W x D x H) mm	Weight kg	PU	Order No.
1031	6	90	100	430 x 300 x 155	6,1	1	0000001031
1032	8	110	100	670 x 300 x 155	8,2	1	0000001032

* Other voltages are available on request.

GFL

2

Multiple Water Baths 1041 / 1042

- Especially suitable for gentle steaming work with columns, Erlenmeyer flasks or beakers. Even after years of continuous operation they remain to be the most reliable laboratory aids.
- Temperature range from approx. 5 °C above ambient to boiling point, temperature regulation through tension thermostat. Heating element protected by over-temperature cut-out.
 - Bath interior, frame with openings and parted perforated floor above the heating element are made of stainless steel.
 - The openings in the frame have a ø of 130 mm and are covered by sets of rings made of heat resistant plastic material.
 - A support rod of 600 mm length and a ø of 12 mm, made of stainless steel, is situated behind each opening. It serves to fix the steaming vessels securely.
 - The adjustable water level regulator is on the left-hand side of the bath. It is included in the standard scope of supply of the units.
 - Outer housing made of electrolytically galvanised sheet steel, powdercoated.
 - Chemical, clinical and biological laboratories, both in research and industry, decide on the multiple water baths whenever special quality and quantity requirements are to be fulfilled.
 - Mains supply: 230 V, 50 / 60 Hz



Type	Openings with sets of rings	Openings- ø mm	Working height mm	Outside dimensions (W x D x H) mm	Power W	Weight kg	PU	Order No.
1041	4	130	90	682 x 232 x 190	1000	12	1	0000001041
1042	6	130	90	982 x 232 x 190	1500	16	1	0000001042

Other voltages are available on request.